



## CleanSpace<sup>®</sup> Fabric Head Harness



<b>PRODUCT CODE</b>	CST1037
<b>PRODUCT NAME</b>	CleanSpace Fabric Head Harness
<b>DESCRIPTION</b>	<p>The CleanSpace fabric head harness (CST1037) is specifically designed to aid in supporting the power unit for optimal comfort. It is designed to be used with the CleanSpace CST PRO (CST1000), CleanSpace CST ULTRA (CST1010) and CleanSpace WORK (CS3000WORK) systems.</p> <p>The CleanSpace fabric head harness attaches easily to connection points on the mask arms. The rear strap of the harness hooks directly onto the power unit for comfortable weight distribution.</p> <p>The CleanSpace fabric head harness is NOT certified intrinsically safe.</p> <p><i>NOTE: The CleanSpace fabric head harness is packaged with the CleanSpace WORK half mask - (Small, Medium and Large) - so is not required to be purchased separately. Please use this product code for the purpose of ordering additional items only.</i></p>
<b>APPROVALS</b>	<p>Certification for the CleanSpace Fabric Head Harness (CST1037) is pending.</p> <p>The CleanSpace WORK System is certified with the CleanSpace HALO Head Harness (CS3008).</p> <p>The CleanSpace CST PRO and CleanSpace CST ULTRA System is certified with the CleanSpace CST Head Harness (CST1021).</p>
<b>FEATURES</b>	<ul style="list-style-type: none"> <li>• Designed for comfort over long periods</li> <li>• Attaches securely to half mask and power unit</li> <li>• All 3 straps are adjustable to fit various head shapes</li> <li>• Fabric material is comfortable to wear under welding helmets and other head protection.</li> </ul>
<b>SPECIFICATIONS</b>	<ul style="list-style-type: none"> <li>• Product Weight: 29 g</li> </ul>
<b>MATERIALS</b>	Polyester   Elastic   High Strength Silicone
<b>CLEANING, USE &amp; STORAGE CONDITIONS</b>	<ul style="list-style-type: none"> <li>• Cleaning: Warm water and mild detergent (neutral pH 6 – 8). Do not use solvents (turpentine or acetone), hot water, bleaching or chemical agents</li> <li>• Use temperature range: -10°C to +45°C (14°F to +113°F) at &lt; 90% relative humidity</li> <li>• Storage conditions: +10°C to +30°C (+50°F to +86°F) at &lt; 75% relative humidity</li> <li>• Store away from direct sunlight, grease and oil</li> </ul>

Australia (Head Office): +61 2 8436 4000 | [sales@cleanspacetechnology.com](mailto:sales@cleanspacetechnology.com)

*Uncontrolled if downloaded or printed from the internet.*

**WWW.CLEANSPACETECHNOLOGY.COM**





**APPLICATIONS**

Suitable for environments which require respiratory protection against airborne particulate contaminants and biohazards.

Examples (use is not limited to these examples):

- Construction – Cutting and grinding concrete, stone, brickwork, steel; sanding plaster, handling cement or other fine dusts
- Woodwork – Cutting, turning or sanding timber
- Agriculture – mowing, reaping and mulching operations; processing or handling animal feeds, grain or other dusty substances
- Healthcare & Laboratories – Handling Biological material, Bacteria, Spores.

**LIMITATIONS**

CleanSpace respirators are air filtering, fan assisted, positive pressure systems and designed to be worn in environments where there is sufficient oxygen to breathe safely. Do not use CleanSpace HALO WORK in environments that are immediately dangerous to life or health (IDLH), to protect against gases/vapours, or in oxygen enriched or deficient atmospheres.

For use in decontamination showers to remove harmful fibres, the fabric harness is not suitable. Use plastic harness CS3008 instead.

**EDUCATION**

Contact [sales@cleanspacetechnology.com](mailto:sales@cleanspacetechnology.com) or visit the CleanSpace website for details.

**WARRANTY**

Visit [www.cleanspacetechnology.com/warranty](http://www.cleanspacetechnology.com/warranty) to read important Warranty information and complete the Warranty Registration Online Form for CleanSpace Products. Consumable parts are warranted up to the point of use, provided they have been stored correctly and are within their expiry date.

CleanSpace recommends filters are replaced regularly.

