

Mould Removal

Why, the Importance of Mould Removal?

There are many health risks caused by exposure to mould, such as, respiratory issues, skin irritations and possible long-term chronic health problems. If the cause of the mould is not eliminated, the mould will reoccur, hence the importance of a thorough cleaning/elimination process.

How to:

- 1. Make sure you are wearing the right PPE, full face respirator (<u>CleanSpace</u>), tyvek suit & gloves.
- 2. Pre-vacuum the surface with a good quality HEPA Vacuum, our recommendation is the <u>Husqvarna HEPA Vacuum</u>.
- 3. Using the <u>Protox Hysan</u> solution (relevant to condition of mould, refer to chart below), apply to the surface using a pump-up sprayer or <u>Gloria Foamer</u> (we recommend our <u>Gloria range</u>) or a window cleaning applicator (usually made of micro fibre) for gyprock walls that are condition 2 mould.
- 4. Next, agitate the solution on surface using one of the following: a motorized made for walls scrubber, hand brush or light agitation with a soft broom or sponge.
- 5. Rinse the treated surface until clean with the remaining Protox Hysan solution using a pump-up sprayer (Gloria range) or a window cleaning applicator (as mentioned above), this way you will remove the greatest number of spores, particles and dirt from the surface.
- 6. Allow 24 Hours for Hysan to oxidize and dry.
- 7. Should any staining be present, apply <u>Protox HP18</u> with <u>Protox Turbo</u> for mould stain removal (note only mix what you need, follow the PPE guidelines on the SDS once the product is mixed will only last for 5 hours, dispose of what you don't need (the toilet is the best place).
- 8. <u>Protox Encapsulator</u> can be applied to areas that you cannot clean (being hard to access) with a <u>Gloria Performance Sprayer</u>, brush or roller. Note: <u>Protox Protect</u> can be applied to protect area from mould growth especially if the problem hasn't been fixed.
- 9. After 24 hours the surface may be wiped with pure water. Note: Hysan can also be spread using a fogger if you need to eliminate odours from a difficult to access space.

CREATING HEALTHY INDOOR ENVIRONMENTS

"On The Job" Industry Experience Since 1995













Outcome:

Effective removal of visible mould and prevention of reoccurring mould. Elimination of airborne mould spores & providing safe quality air for a healthier living space. Reduced risk of health issues caused by exposure to mould.

Hysan Ratio

Heavy Mould (Condition 3) = 1:1Medium Mould (Condition 2) = 1:2Light Mould

(Condition 1) = 1:3

CREATING HEALTHY INDOOR ENVIRONMENTS

"On The Job" Industry Experience Since 1995









